

LFFC-P2.5 front outdoor maintenance led display



Module & cabinet:



Features:

- Space-saving, without service access at the backside;
- Thinner steel structure;
- Lighter steel structure;
- Beautiful appearance;
- Easy to install;
- Save materials;
- Open the cabinet to maintain;



Application:

outdoor advertising
 government project
 athletic contest
 Shopping Guide
 commercial real estat

Technical Specifications:

| Pixel Pitch | P2.5 |
|--|-------------------------------|
| LED type | SMD1415 |
| Pixel configuration | 3-in-1 SMD |
| Pixel density | 160,000 pixels/m ² |
| Module dimension(W*H) | 160*160mm |
| Module resolution | 64*64dots |
| Drive Method | 1/16 scan |
| Cabinet size (W*H) | 640*640mm or Customized |
| Cabinet depth | 136mm |
| Cabinet material | Iron or aluminum |
| Cabinet weight | 16kg/pcs |
| Brightness | ≥6800 cd/m ² |
| Best Viewing Distance | 2.5m to 25m |
| Viewing Angle | 140 * 140 |
| Grey Level | 14 Bit |
| Refresh Rate | ≥1920HZ |
| Power consumption(Avg.) | 200 w/cabinet |
| Power consumption(Max.) | 600 w/cabinet |
| Humidity-operating | 10% ~ 95% |
| Operating Temperature | -20° - 50° C |
| Screen life | ≥100000 hours |
| Controlling System | Synch or Async |
| Certificates | CE,RoHs,FCC,UL |
| Ingress Protection (IP) | IP65 |
| Warranty | 2 Years |
| Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to SZLEDWORLD. | |