

LFFC-P3 front outdoor maintenance led display



Module & cabinet:



Features:

- Space-saving, without service access at the backside;
- Thinner steel structure;
- Lighter steel structure;
- Beautiful appearance;
- Easy to install;
- Save materials;
- Open the cabinet to maintain;



Application:

outdoor advertising
 government project
 athletic contest
 Shopping Guide
 commercial real estat

Technical Specifications:

Pixel Pitch	P3
LED type	SMD1921
Pixel configuration	3-in-1 SMD
Pixel density	111,111 pixels/m ²
Module dimension(W*H)	192*192mm
Module resolution	64*64dots
Drive Method	1/16 scan
Cabinet size (W*H)	768*768mm or Customized
Cabinet depth	136mm
Cabinet material	Iron or aluminum
Cabinet weight	23kg/pcs
Brightness	≥5500 cd/m ²
Best Viewing Distance	3m to 30m
Viewing Angle	140 * 140
Grey Level	14 Bit
Refresh Rate	≥1920HZ
Power consumption(Avg.)	267 w/cabinet
Power consumption(Max.)	800 w/cabinet
Humidity-operating	10% ~ 95%
Operating Temperature	-20° - 50° C
Screen life	≥100000 hours
Controlling System	Synch or Async
Certificates	CE,RoHs,FCC,UL
Ingress Protection (IP)	IP65
Warranty	2 Years
Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to SZLEDWORLD.	