

LFFC-P6.67 front outdoor maintenance led display



Module & cabinet:



Features:

- Space-saving, without service access at the backside;
- Thinner steel structure;
- Lighter steel structure;
- Beautiful appearance;
- Easy to install;
- Save materials;
- Open the cabinet to maintain;



Application:

outdoor advertising
 government project
 athletic contest
 Shopping Guide
 commercial real estat

Technical Specifications:

Pixel Pitch	P6.67
LED type	SMD 3535
Pixel configuration	3-in-1 SMD
Pixel density	22,500 pixels/m2
Module dimension(W*H)	320*160mm
Module resolution	48*24dots
Drive Method	1/6 scan
Cabinet size (W*H)	960*960mm or Customized
Cabinet depth	136mm
Cabinet material	Iron or aluminum
Cabinet weight	36kg/pcs
Brightness	6000 cd/m2
Best Viewing Distance	6m to 60m
Viewing Angle	140 * 140
Grey Level	14 Bit
Refresh Rate	≥1920HZ
Power consumption(Avg.)	270w/cabinet
Power consumption(Max.)	800w/cabinet
Humidity-operating	10% ~ 95%
Operating Temperature	-20° - 50° C
Screen life	≥100000 hours
Controlling System	Synch or Async
Certificates	CE,RoHs,FCC,UL
Ingress Protection (IP)	IP65
Warranty	2 Years
Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to SZLEDWORLD.	