

## LFFL-P3.125 front outdoor maintenance led display



### Cabinets:



### Features:

- Space-saving, without service access at the backside;
- Thinner steel structure;
- Lighter steel structure;
- Beautiful appearance;
- Easy to install;
- Save materials;
- Fast maintenance;



## Application:

outdoor advertising  
  government project  
  athletic contest  
  Shopping Guide  
  commercial real estate

## Technical Specifications:

Pixel Pitch	P3.125
LED type	SMD1415
Pixel configuration	3-in-1 SMD
Pixel density	102,400 pixels/m <sup>2</sup>
Module dimension(W*H)	250*250mm
Module resolution	80*80dots
Drive Method	1/10 scan
Cabinet size (W*H)	1000*1000mm or Customized
Cabinet depth	136mm
Cabinet material	Iron or aluminum
Cabinet weight	40kg/pcs
Brightness	≥5000 cd/m <sup>2</sup>
Best Viewing Distance	3m to 30m
Viewing Angle	140° * 140°
Grey Level	14 Bit
Refresh Rate	≥1920HZ
Power consumption(Avg.)	400w/cabinet
Power consumption(Max.)	1200w/cabinet
Humidity-operating	10% ~ 95%
Operating Temperature	-20° - 50° C
Screen life	≥100000 hours
Controlling System	Synch or Async
Certificates	CE,RoHs,FCC,UL
Ingress Protection (IP)	IP65
Warranty	2 Years

Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to SZLEDWORLD.