


## LFFS-P10 front outdoor maintenance led display



### Cabinets:



### Features:

- Space-saving, without service access at the backside;
- Thinner steel structure;
- Lighter steel structure;
- Beautiful appearance;
- Easy to install;
- Save materials;
- Cost-effective;



## Application:

outdoor advertising  
  government project  
  athletic contest  
  Shopping Guide  
  commercial real estate

## Technical Specifications:

Pixel Pitch	P10
LED type	SMD3535
Pixel configuration	3-in-1 SMD
Pixel density	10,000 pixels/m <sup>2</sup>
Module dimension(W*H)	320*160mm
Module resolution	32*16dots
Drive Method	1/2 scan
Cabinet size (W*H)	960*960mm or Customized
Cabinet depth	136mm
Cabinet material	Iron or aluminum
Cabinet weight	36kg/pcs
Brightness	≥6000 cd/m <sup>2</sup>
Best Viewing Distance	10m to 100m
Viewing Angle	140 * 140
Grey Level	14 Bit
Refresh Rate	≥1920HZ
Power consumption(Avg.)	300w/cabinet
Power consumption(Max.)	900w/cabinet
Humidity-operating	10% ~ 95%
Operating Temperature	-20° - 50° C
Screen life	≥100000 hours
Controlling System	Synch or Asynch
Certificates	CE,RoHs,FCC,UL
Ingress Protection (IP)	IP65
Warranty	2 Years

Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to SZLEDWORLD.