

LFT-1024-P8 thin outdoor fixed led display



Features:

- Ultra-thin, 102mm;
- Excellent heat dissipation;
- Lightweight, 25kg/cabinet;
- Convenient installation;
- High precision, 0.02mm;
- Excellent shielding;
- Super reliability;
- Good anti-rust performance;



Application:

outdoor advertising
 government project
 athletic contest
 Shopping Guide
 commercial real estate

Technical Specifications:

Pixel Pitch	P8
LED type	SMD 3535
Pixel configuration	3-in-1 SMD
Pixel density	15,625 pixels/m ²
Module dimension(W*H)	256*128mm
Module resolution	32*16dots
Drive Method	1/4 scan
Cabinet size (W*H)	1024*768mm
Cabinet depth	102mm
Cabinet material	magnesium or aluminum alloy
Cabinet weight	25kg/pcs
Brightness	≥5500 cd/m ²
Best Viewing Distance	8m to 80m
Viewing Angle	140 * 140
Grey Level	14 Bit
Refresh Rate	≥1920HZ
Power consumption(Avg.)	270w/cabinet
Power consumption(Max.)	800w/cabinet
Humidity-operating	10% ~ 95%
Operating Temperature	-20° - 50° C
Screen life	≥100000 hours
Controlling System	Sync or Async
Certificates	CE,RoHs,FCC,UL
Ingress Protection (IP)	IP65
Warranty	2 Years

Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to SZLEDWORLD.