

LFT-768 - P6 thin outdoor fixed led display



Features:

- Ultra-thin, 102mm;
- Excellent heat dissipation;
- Lightweight, 18kg/cabinet;
- Convenient installation;
- High precision, 0.02mm;
- Excellent shielding;
- Super reliability;
- Good anti-rust performance;



Application:

outdoor advertising
 government project
 athletic contest
 Shopping Guide
 commercial real estate

Technical Specifications:

| Pixel Pitch | P6 |
|-------------------------|------------------------------|
| LED type | SMD 3535 |
| Pixel configuration | 3-in-1 SMD |
| Pixel density | 27,777 pixels/m ² |
| Module dimension(W*H) | 192*192mm |
| Module resolution | 32*32dots |
| Drive Method | 1/8 scan |
| Cabinet size (W*H) | 768*768mm |
| Cabinet depth | 102mm |
| Cabinet material | magnesium alloy |
| Cabinet weight | 18kg/pcs |
| Brightness | ≥5000 cd/m ² |
| Best Viewing Distance | 6m to 60m |
| Viewing Angle | 140 * 140 |
| Grey Level | 14 Bit |
| Refresh Rate | ≥1920HZ |
| Power consumption(Avg.) | 200w/cabinet |
| Power consumption(Max.) | 600w/cabinet |
| Humidity-operating | 10% ~ 95% |
| Operating Temperature | -20° - 50° C |
| Screen life | ≥100000 hours |
| Controlling System | Sync or Async |
| Certificates | CE,RoHs,FCC,UL |
| Ingress Protection (IP) | IP65 |
| Warranty | 2 Years |

Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to SZLEDWORLD.