

# Perimeter led display-P10



## Features:

- The cabinet comes with supporting legs, no other installation structure is required;
- Soft top cover and soft maskshield effectively protect the athlete from an injury
- Uniform color and high contrast ratio,Bringing up fresh and natureal image ;
- Low power consumption and fine heat release ;
- Super wide viewing angle increasing Its value by covering more audience
- No deformation under sunlight by the Use of anti-UV modules
- High protection grade of IP65 achieved by Patented mask design with waterproof and dustproof function
- Safe and reliable operation ensured by Stable signal and power supply



## Application:

outdoor advertising  
  government project  
  athletic contest

## Technical Specifications:

| Pixel Pitch             | P10                          |
|-------------------------|------------------------------|
| LED type                | SMD 3535                     |
| Pixel configuration     | 3-in-1 SMD                   |
| Pixel density           | 10,000 pixels/m <sup>2</sup> |
| Module dimension(W*H)   | 320*160mm                    |
| Module resolution       | 32*16dots                    |
| Mask                    | soft                         |
| Drive Method            | 1/2 scan                     |
| Cabinet size (W*H)      | 960/1280*960mm               |
| Cabinet depth           | 102mm                        |
| Cabinet material        | magnesium or aluminum alloy  |
| Cabinet weight          | 25kg/pcs                     |
| Mounting legs           | Middle leg                   |
| Protective cover        | Soft tophat                  |
| Brightness              | 6500 cd/m <sup>2</sup>       |
| Best Viewing Distance   | 10m to 100m                  |
| Viewing Angle           | 140 * 140                    |
| Grey Level              | 14 Bit                       |
| Refresh Rate            | ≥1920HZ                      |
| Power consumption(Avg.) | 300w/cabinet                 |
| Power consumption(Max.) | 900w/cabinet                 |
| Humidity-operating      | 10% ~ 95%                    |
| Operating Temperature   | -20° - 50° C                 |
| Screen life             | ≥100000 hours                |
| Controlling System      | Sync or Async                |
| Certificates            | CE,RoHs,FCC,UL               |
| Ingress Protection (IP) | IP65                         |
| Warranty                | 2 Years                      |

Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to SZLEDWORLD.