

# Perimeter led display-P6.67



## Features:

- The cabinet comes with supporting legs, no other installation structure is required;
- Soft top cover and soft maskshield effectively protect the athlete from an injury
- Uniform color and high contrast ratio,Bringing up fresh and natureal image ;
- Low power consumption and fine heat release ;
- Super wide viewing angle increasing Its value by covering more audience
- No deformation under sunlight by the Use of anti-UV modules
- High protection grade of IP65 achieved by Patented mask design with waterproof and dustproof function
- Safe and reliable operation ensured by Stable signal and power supply



## Application:

outdoor advertising  
  government project  
  athletic contest

## Technical Specifications:

Pixel Pitch	P6.67
LED type	SMD 3535
Pixel configuration	3-in-1 SMD
Pixel density	22,500 pixels/m <sup>2</sup>
Module dimension(W*H)	320*160mm
Module resolution	48*24dots
Mask	soft
Drive Method	1/6 scan
Cabinet size (W*H)	960/1280*960mm
Cabinet depth	102mm
Cabinet material	magnesium or aluminum alloy
Cabinet weight	25kg/pcs
Mounting legs	Middle leg
Protective cover	Soft tophat
Brightness	6000 cd/m <sup>2</sup>
Best Viewing Distance	6m to 60m
Viewing Angle	140 * 140
Grey Level	14 Bit
Refresh Rate	≥1920HZ
Power consumption(Avg.)	270w/cabinet
Power consumption(Max.)	800w/cabinet
Humidity-operating	10% ~ 95%
Operating Temperature	-20° - 50° C
Screen life	≥100000 hours
Controlling System	Sync or Async
Certificates	CE,RoHs,FCC,UL
Ingress Protection (IP)	IP65
Warranty	2 Years

Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to SZLEDWORLD.