


Outdoor fixed led display (ESP1000 Series)



Features:

- Common cathode energy-saving technology, more than 40% energy-saving than traditional outdoor LED display;
- Aluminum material, good heat dissipation, no need for fans;
- High brightness, the highest brightness can reach 5500nits~10000nits, adapt to strong light;
- Stable, integrated design, stability increased by 60%;
- Ultra-thin outdoor cabinet;
- Ultra-light cabinet, 25kg/cabinet, easy maintenance



Cabinets



Cabinets



Application:

☐ outdoor advertising
 ☐ government project
 ☐ athletic contest
 ☐ Shopping Guide
 ☐ commercial real estate

Technical Specifications:

Product model	P6.25
Pixel pitch	6.25mm
Module size	500*250mm
Module resolution	80*40
Pixel composition	SMD2727
Scanning method	1/5S
Refresh rate	≥3840Hz
Gray scale	14bit
Brightness	≥6000cd/m ²
Viewing angle(H/V)	140/140
Module current	≤16A
Module weight	Alu module chassis 1400g Plastic module chassis
Cabinet size	1000mm*1000mm*75mm
Cabinet weight	25Kg
Maintain connection method	Hub connection; Front&back maintain method
Cabinet resolution	160*160
IP grade (front/back)	IP65
Input voltage	110-220V;AC±10%
Working temperature	-20°C -- +65°C
Aver power consumption	Common cathode screen : Aver 180w/m ² ; Regular screens: Aver 280w/m ²
Max power consumption	Common cathode screen : Aver 550w/m ² ; Regular screens: Aver 750w/m ²
Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to SZLEDWORLD.	