

Application:

☐ Stage Performance
 ☐ Conference
 ☐ Celebration
 ☐ banquet
 ☐ exhibition

Technical Specifications(FRI500 Series indoor):

Pixel Pitch	P1.953
LED type	SMD1515
Pixel configuration	3-in-1 SMD
Pixel density	262,144 pixels/m2
Module dimension(W*H)	250*250mm
Module resolution	128*128dots
Drive Method	1/32 scan
Maintenance	back
Cabinet size (W*H)	500*500mm
Cabinet depth	85mm
Cabinet material	Aluminum
Cabinet weight	6.7kg/pcs
Brightness	700 cd/m2
Best Viewing Distance	2 m to 20m
Viewing Angle	140 * 140
Grey Level	14~22bits
Refresh Rate	≥3840HZ
Power consumption(Avg.)	50w/cabinet
Power consumption(Max.)	140w/cabinet
Humidity-operating	10% ~ 95%
Operating Temperature	-20° - 50° C
Screen life	≥100000 hours
Controlling System	Sync or Async
Certificates	CE,RoHS,FCC,UL
Ingress Protection (IP)	IP31
Warranty	2 Years
Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to SZLEDWORLD.	