

Application:

☐ Stage Performance
 ☐ Conference
 ☐ Celebration
 ☐ banquet
 ☐ exhibition

Technical Specifications(FRI500 Series indoor&outdoor):

Pixel Pitch	P2.604(indoor)	P2.604(outdoor)
LED type	SMD2121/1515	SMD1415
Pixel configuration	3-in-1 SMD	3-in-1 SMD
Pixel density	147,456 pixels/m2	147,456 pixels/m2
Module dimension(W*H)	250*250mm	250*250mm
Module resolution	96*96dots	96*96dots
Drive Method	1/32 scan	1/24 scan
Maintenance	back	back
Cabinet size (W*H)	500*500mm	500*500mm
Cabinet depth	85mm	85mm
Cabinet material	Aluminum	Aluminum
Cabinet weight	6.7kg/pcs	7.7kg/pcs
Brightness	800 cd/m2	4300 cd/m2
Best Viewing Distance	2.5m to 25m	2.5m to 25m
Viewing Angle	140 * 140	140 * 140
Grey Level	14~22bits	14~22bits
Refresh Rate	≥3840HZ	≥3840HZ
Power consumption(Avg.)	60w/cabinet	70w/cabinet
Power consumption(Max.)	180w/cabinet	200w/cabinet
Humidity-operating	10% ~ 95%	10% ~ 95%
Operating Temperature	-20° - 50° C	-20° - 50° C
Screen life	≥100000 hours	≥100000 hours
Controlling System	Sync or Async	Sync or Async
Certificates	CE,RoHS,FCC,UL	CE,RoHS,FCC,UL
Ingress Protection (IP)	IP31	IP65
Warranty	2 Years	2 Years
Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to SZLEDWORLD.		