

Application:

☐ Major Football Match
 ☐ Playground
 ☐ Stadium
 ☐ Outdoor Sports Field
 ☐ Rugby Match

Technical Specifications(EPS400 Series Led display):

Pixel Pitch	P5
LED type	SMD1921
Pixel configuration	3-in-1 SMD
Pixel density	40,000pixels/m ²
Module dimension(W*H)	400*300mm
Module resolution	80*60dots
Drive Method	1/6 scan
Maintenance	Front & Rear
Cabinet size (W*H)	1600*900mm
Cabinet depth	75mm
Cabinet material	Aluminum
Cabinet weight	51.2kg/pcs
Brightness	≥6000 cd/m ²
Best Viewing Distance	5m to 50m
Viewing Angle	140 * 140
Grey Level	16bits
Refresh Rate	≥7680HZ
Power consumption(Avg.)	Common cathode screen: Aver 180W/m ² ; Regular screens: Aver 350W/m ²
Power consumption(Max.)	Common cathode screen: Aver 550W/m ² ; Regular screens: Aver 800W/m ²
Humidity-operating	10% ~ 95%
Operating Temperature	-20° - 60° C
Screen life	≥100000 hours
Controlling System	Sync or Async
Certificates	CE,RoHS,FCC,UL
Ingress Protection (IP)	IP65
Warranty	2 Years
Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to SZLEDWORLD.	