

Application:

☐ Stage Performance
 ☐ Major sports events
 ☐ Hotel lobby
 ☐ Billboard
 ☐ exhibition

Technical Specifications(LFT1280 Series Led display):

Pixel Pitch	P4
LED type	SMD 1921
Pixel configuration	3-in-1 SMD
Pixel density	62,500 pixels/m ²
Module dimension(W*H)	320*160mm
Module resolution	80*40dots
Drive Method	1/10 scan
Maintenance	Rear
Cabinet size (W*H)	1280X960mm
Cabinet depth	102mm
Cabinet material	Magnesium
Cabinet weight	28kg/pcs
Brightness	≥5500 cd/m ²
Best Viewing Distance	4m to 40m
Viewing Angle	140° * 140°
Grey Level	16bits
Refresh Rate	≥3840HZ
Power consumption(Avg.)	326w/sqm
Power consumption(Max.)	976w/sqm
Humidity-operating	10% ~ 95%
Operating Temperature	-20° - 60° C
Screen life	≥100000 hours
Controlling System	Sync or Async
Certificates	CE,RoHS,FCC,UL
Ingress Protection (IP)	IP65
Warranty	2 Years
Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to SZLEDWORLD.	