

## Application:

☐ Stage Performance
 ☐ Major sports events
 ☐ Hotel lobby
 ☐ Billboard
 ☐ exhibition

## Technical Specifications(LFT1280 Series Led display):

| Pixel Pitch                                                                                                                      | P6.67                        |
|----------------------------------------------------------------------------------------------------------------------------------|------------------------------|
| LED type                                                                                                                         | SMD3535                      |
| Pixel configuration                                                                                                              | 3-in-1 SMD                   |
| Pixel density                                                                                                                    | 22,500 pixels/m <sup>2</sup> |
| Module dimension(W*H)                                                                                                            | 320*160mm                    |
| Module resolution                                                                                                                | 48*24dots                    |
| Drive Method                                                                                                                     | 1/6 scan                     |
| Maintenance                                                                                                                      | Rear                         |
| Cabinet size (W*H)                                                                                                               | 1280X960mm                   |
| Cabinet depth                                                                                                                    | 102mm                        |
| Cabinet material                                                                                                                 | Magnesium                    |
| Cabinet weight                                                                                                                   | 28kg/pcs                     |
| Brightness                                                                                                                       | ≥5000 cd/m <sup>2</sup>      |
| Best Viewing Distance                                                                                                            | 6.6m to 66m                  |
| Viewing Angle                                                                                                                    | 140° * 140°                  |
| Grey Level                                                                                                                       | 16bits                       |
| Refresh Rate                                                                                                                     | ≥3840HZ                      |
| Power consumption(Avg.)                                                                                                          | 326w/sqm                     |
| Power consumption(Max.)                                                                                                          | 976w/sqm                     |
| Humidity-operating                                                                                                               | 10% ~ 95%                    |
| Operating Temperature                                                                                                            | -20° - 60° C                 |
| Screen life                                                                                                                      | ≥100000 hours                |
| Controlling System                                                                                                               | Sync or Async                |
| Certificates                                                                                                                     | CE,RoHS,FCC,UL               |
| Ingress Protection (IP)                                                                                                          | IP65                         |
| Warranty                                                                                                                         | 2 Years                      |
| Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to SZLEDWORLD. |                              |