

## Application:

☐ Press Conference
 ☐ Wedding
 ☐ Outdoor Music Festival
 ☐ Store
 ☐ Exhibition Hall

## Technical Specifications(RHD Series Led Display P2.604):

| Pixel Pitch             | P2.604(indoor)        | P2.604(outdoor)       |
|-------------------------|-----------------------|-----------------------|
| LED type                | SMD1515               | SMD1415               |
| Pixel configuration     | 3-in-1 SMD            | 3-in-1 SMD            |
| Pixel density           | 147,456 pixels/m2     | 147,456 pixels/m2     |
| Module dimension(W*H)   | 250*500mm             | 250*500mm             |
| Module resolution       | 96*192dots            | 96*192dots            |
| Drive Method            | 1/32 scan             | 1/24 scan             |
| Maintenance             | Front & Rear          | Front & Rear          |
| Cabinet size (W*H)      | 500*500mm             | 500*1000mm            |
| Cabinet depth           | 76.3mm                | 76.3mm                |
| Cabinet material        | Aluminum              | Aluminum              |
| Cabinet weight          | 9.5kg/pcs             | 15kg/pcs              |
| Brightness              | 800 cd/m <sup>2</sup> | 4500cd/m <sup>2</sup> |
| Best Viewing Distance   | 2.6m to 26m           | 2.6m to 26m           |
| Viewing Angle           | 160 * 160             | 140 * 140             |
| Grey Level              | 16bits                | 14bits                |
| Refresh Rate            | ≥3840HZ               | ≥3840HZ               |
| Power consumption(Avg.) | 220w/sqm              | 280w/cabinet          |
| Power consumption(Max.) | 500w/sqm              | 650w/cabinet          |
| Humidity-operating      | 10% ~ 95%             | 10% ~ 95%             |
| Operating Temperature   | -20° - 50° C          | -20° - 50° C          |
| Screen life             | ≥100000 hours         | ≥100000 hours         |
| Controlling System      | Sync or Async         | Sync or Async         |
| Certificates            | CE,RoHS,FCC,UL        | CE,RoHS,FCC,UL        |
| Ingress Protection (IP) | IP40/IP21             | IP65                  |
| Warranty                | 2 Years               | 2 Years               |

Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to SZLEDWORLD.