

Application:

☐ Press Conference
 ☐ Wedding
 ☐ Outdoor Music Festival
 ☐ Store
 ☐ Exhibition Hall

Technical Specifications(RHD Series Led Display P2.97):

Pixel Pitch	P2.97(indoor)	P2.97(outdoor)
LED type	SMD1515/2121	SMD1415
Pixel configuration	3-in-1 SMD	3-in-1 SMD
Pixel density	112,896 pixels/m2	112,896 pixels/m2
Module dimension(W*H)	250*500mm	250*500mm
Module resolution	84*168dots	84*168dots
Drive Method	1/21 scan	1/21 scan
Maintenance	Front & Rear	Front & Rear
Cabinet size (W*H)	500*500mm	500*1000mm
Cabinet depth	76.3mm	76.3mm
Cabinet material	Aluminum	Aluminum
Cabinet weight	9.5kg/pcs	15kg/pcs
Brightness	800 cd/m ²	4500cd/m ²
Best Viewing Distance	3m to 30m	3m to 30m
Viewing Angle	160 * 160	140 * 140
Grey Level	16bits	14bits
Refresh Rate	≥3840HZ	≥3840HZ
Power consumption(Avg.)	220w/sqm	280w/cabinet
Power consumption(Max.)	500w/sqm	650w/cabinett
Humidity-operating	10% ~ 95%	10% ~ 95%
Operating Temperature	-20° - 50° C	-20° - 50° C
Screen life	≥100000 hours	≥100000 hours
Controlling System	Sync or Async	Sync or Async
Certificates	CE,RoHS,FCC,UL	CE,RoHS,FCC,UL
Ingress Protection (IP)	IP40/IP21	IP65
Warranty	2 Years	2 Years

Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to SZLEDWORLD.