

Application:

☐ Press Conference
 ☐ Wedding
 ☐ Outdoor Music Festival
 ☐ Store
 ☐ Exhibition Hall

Technical Specifications(RHD Series Led Display P3.91):

Pixel Pitch	P3.91 (indoor)	P3.91 (outdoor)
LED type	SMD2121	SMD1921
Pixel configuration	3 in 1 SMD	3 in 1 SMD
Pixel density	65,536 pixels/m ²	65,536 pixels/m ²
Module dimension(W*H)	250*500mm	250*500mm
Module resolution	64*128dots	64*128dots
Drive Method	1/16 scan	1/16 scan
Maintenance	Front & Rear	Front & Rear
Cabinet size (W*H)	500*500mm	500*1000mm
Cabinet depth	76.3mm	76.3mm
Cabinet material	Aluminum	Aluminum
Cabinet weight	9.5kg/pcs	15kg/pcs
Brightness	800 cd/m ²	4500cd/m ²
Best Viewing Distance	4m to 40m	4m to 40m
Viewing Angle	160 * 160	140 * 140
Grey Level	16bits	14bits
Refresh Rate	7680HZ	7680HZ
Power consumption(Avg.)	220w/sqm	280w/cabinet
Power consumption(Max.)	500w/sqm	650w/cabinet
Humidity-operating	10% ~ 95%	10% ~ 95%
Operating Temperature	-20° - 50° C	-20° - 50° C
Screen life	≥100000 hours	≥100000 hours
Controlling System	Sync or Async	Sync or Async
Certificates	CE,RoHS,FCC,UL	CE,RoHS,FCC,UL
Ingress Protection (IP)	IP40/IP21	IP65
Warranty	2 Years	2 Years
Notes:Specifications are for reference only.Please contact our salesperson for details.All rights are reserved to SZLEDWORLD.		