

Application:

☐ Press Conference
 ☐ Wedding
 ☐ Outdoor Music Festival
 ☐ Store
 ☐ Exhibition Hall

Technical Specifications(RHL Series Led Display P2.97):

Pixel Pitch	P2.97(indoor)	P2.97(outdoor)
LED type	SMD2121/1515	SMD1415
Pixel configuration	3-in-1 SMD	3-in-1 SMD
Pixel density	112,896 pixels/m2	112,896 pixels/m2
Module dimension(W*H)	250*250mm	250*250mm
Module resolution	84*84dots	84*84dots
Drive Method	1/21 or 1/28 scan	1/21 scan
Maintenance	Front & Rear	Front & Rear
Cabinet size (W*H)	500*500mm	500*500mm
Cabinet depth	85mm	87mm
Cabinet material	Aluminum	Aluminum
Cabinet weight	6.5kg/pcs	7.5kg/pcs
Brightness	800 cd/m ²	4500 cd/m ²
Best Viewing Distance	3m to 30m	3m to 30m
Viewing Angle	160 * 160	160 * 160
Grey Level	16bits	16bits
Refresh Rate	≥3840HZ	≥3840HZ
Power consumption(Avg.)	200w/cabinet	135w/cabinet
Power consumption(Max.)	400w/cabinet	400w/cabinet
Humidity-operating	10% ~ 95%	10% ~ 95%
Operating Temperature	-40° - 60° C	-40° - 60° C
Screen life	≥100000 hours	≥100000 hours
Controlling System	Sync or Async	Sync or Async
Certificates	CE,RoHS,FCC,UL	CE,RoHS,FCC,UL
Ingress Protection (IP)	IP31	IP65
Warranty	2 Years	2 Years

Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to SZLEDWORLD.