


EPS480 Series Energy-Saving Perimeter LED Display




Module & cabinet:



960*960mm cabinet



480*320 module



Sports led display

Features:

- Suitable for P6.67, P8, P10 pixel pitch;
- Die-cast magnesium alloy cabinet;
- Energy-Saving;
- IP65 protection rating;
- Light weight: 26.5kg ;
- Thin cabinet: 96mm ;
- 2-Year Warranty;
- Seamless Splicing.



Application:

☐ Major Football Match
 ☐ Playground
 ☐ Stadium
 ☐ Outdoor Sports Field
 ☐ Rugby Match

Technical Specifications(EPS480 Series Led display):

Pixel Pitch	P6.67	P8	P10
LED type	SMD2727	SMD2727	SMD2727
Pixel configuration	3-in-1 SMD	3-in-1 SMD	3-in-1 SMD
Pixel density	22,500 pixels/m ²	15,625 pixels/m ²	10,000 pixels/m ²
Module dimension(W*H)	480*320mm	480*320mm	480*320mm
Module resolution	72*48dots	60*40dots	48*32dots
Drive Method	1/6 scan	1/5 scan	1/2 scan
Maintenance	Front & Rear	Front & Rear	Front & Rear
Cabinet size (W*H)	960*960mm	960*960mm	960*960mm
Cabinet depth	96mm	96mm	96mm
Cabinet material	Magnesium	Magnesium	Magnesium
Cabinet weight	26.5kg/pcs	26.5kg/pcs	26.5kg/pcs
Brightness	≥5500 cd/m ²	≥6000 cd/m ²	≥6500 cd/m ²
Best Viewing Distance	6.6m to 66m	8m to 80m	10m to 100m
Viewing Angle	140 * 140	140 * 140	140 * 140
Grey Level	14bits	14bits	14bits
Refresh Rate	≥3840HZ	≥3840HZ	≥3840HZ
Power consumption(Avg.)	Common Cathode: 180 W/m ² ; Common Anode: 320 W/m ²	Common Cathode: 180 W/m ² ; Common Anode: 320 W/m ²	Common Cathode: 180 W/m ² ; Common Anode: 320 W/m ²
Power consumption(Max.)	Common Cathode: 550 W/m ² ; Common Anode: 750 W/m ²	Common Cathode: 550 W/m ² ; Common Anode: 750 W/m ²	Common Cathode: 550 W/m ² ; Common Anode: 750 W/m ²
Humidity-operating	10% ~ 95%	10% ~ 95%	10% ~ 95%
Operating Temperature	-20° - 60° C	-20° - 60° C	-20° - 60° C
Screen life	≥100000 hours	≥100000 hours	≥100000 hours
Controlling System	Sync or Async	Sync or Async	Sync or Async
Certificates	CE, RoHS, FCC, UL	CE, RoHS, FCC, UL	CE, RoHS, FCC, UL
Ingress Protection (IP)	IP65	IP65	IP65
Warranty	2 Years	2 Years	2 Years

Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to SZLEDWORLD.