

## Application:

☐ Major Football Match
 ☐ Playground
 ☐ Stadium
 ☐ Outdoor Sports Field
 ☐ Rugby Match

## Technical Specifications(EPS480 Series Led display):

| Pixel Pitch                               | P8                                                                        |
|-------------------------------------------|---------------------------------------------------------------------------|
| LED type                                  | SMD2727                                                                   |
| Pixel configuration                       | 3-in-1 SMD                                                                |
| <a href="#">Pixel density</a>             | 15,625 pixels/m <sup>2</sup>                                              |
| Module dimension(W*H)                     | 480*320mm                                                                 |
| Module resolution                         | 60*40dots                                                                 |
| Drive Method                              | 1/5 scan                                                                  |
| Maintenance                               | Front & Rear                                                              |
| Cabinet size (W*H)                        | 960*960mm                                                                 |
| Cabinet depth                             | 96mm                                                                      |
| Cabinet material                          | Magnesium                                                                 |
| Cabinet weight                            | 26.5kg/pcs                                                                |
| Brightness                                | ≥6000 cd/m <sup>2</sup>                                                   |
| <a href="#">Best Viewing Distance</a>     | 8m to 80m                                                                 |
| <a href="#">Viewing Angle</a>             | 140 * 140                                                                 |
| Grey Level                                | 14bits                                                                    |
| <a href="#">Refresh Rate</a>              | ≥3840HZ                                                                   |
| Power consumption(Avg.)                   | Common Cathode: 180 W/m <sup>2</sup> ; Common Anode: 320 W/m <sup>2</sup> |
| Power consumption(Max.)                   | Common Cathode: 550 W/m <sup>2</sup> ; Common Anode: 750 W/m <sup>2</sup> |
| Humidity-operating                        | 10% ~ 95%                                                                 |
| Operating Temperature                     | -20° - 60° C                                                              |
| Screen life                               | ≥100000 hours                                                             |
| <b><a href="#">Controlling System</a></b> | <b>Sync or Async</b>                                                      |
| Certificates                              | CE, RoHS, FCC, UL                                                         |
| Ingress Protection (IP)                   | IP65                                                                      |
| Warranty                                  | 2 Years                                                                   |

Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to SZLEDWORLD.