

IFS Series Indoor Fixed Soft Connection LED Display



Cabinet:



960 × 960mm



960 × 960mm



Cabinets

Features:

- Pixel pitch: P2,P2.5,P2.6,P2.9,3.076,P3.9,P4,P5 etc;
- Soft connection;
- Front and rear maintenance;
- Iron or aluminium LED cabinet;
- Fanless design;
- Light weight: 22kg/sqm
- Thin cabinet: 80mm ;
- Cabinet Size: standard 960*960mm or customised.



Application:

☐ Store
 ☐ Conference
 ☐ Auditorium
 ☐ Studio
 ☐ Exhibition

Technical Specifications(IFS Series):

Pixel Pitch	P2mm	P2.5mm	P2.6mm	P2.9mm	P3.076mm	P3.9mm	P4mm	P5mm
LED type	SMD1515	SMD2121	SMD1515	SMD2121/1515	SMD2121	SMD2121	SMD2121	SMD2121
Configuration	SMD 3-in-1	SMD 3-in-1	SMD 3-in-1	SMD 3-in-1	SMD 3-in-1	SMD 3-in-1	SMD 3-in-1	SMD 3-in-1
Pixel Density	250,000	160,000	147,456	112,896	105,625	65,536	62,500	40,000
Module Size(mm)	320x160	320x160	250x250	250x250	320x160	250x250	320x160	320x160
Pixels/Module	160x80	128x64	96x96	84x84	104x52	64x64	80x40	64x32
Cabinet Size(mm)	960x960	960x960	1000x1000	1000x1000	960x960	1000x1000	960x960	960x960
Pixels/Cabinet	480x480	384x384	384x384	336x336	208x208	256x256	160x160	192x192
Cabinet Weight	20KG	20KG	22KG	22KG	20KG	22KG	20KG	20KG
Brightness	700nits	700nits	800nits	800nits	700nits	800nits	700nits	700nits
Viewing Distance	>2m	>2.5m	>2.6m	>2.9m	>3m	>3.9m	>4m	>5m
Power Consumption	Max: 500	Max: 500	Max: 800	Max: 800	Max: 500	Max: 800	Max: 500	Max: 500
(W/m ²)	Ave:170	Ave: 170	Ave: 268	Ave: 268	Ave: 170	Ave: 268	Ave: 170	Ave: 170
Driver Mode	1/40 scan	1/32 scan	1/32 scan	1/28 or 1/21 scan	1/26 scan	1/16 scan	1/20 scan	1/16 scan
Cabinet Material	Iron or Aluminium							
Refresh Rate	3840Hz ~7680Hz							
LED Life	100,000 hours							
Supply Voltage	AC220V/50HZ; AC110V/60HZ							
Operating Temperature	-20℃ ~ +40℃							
Operating Humidity	10% - 90%							
Viewing Angle	H: 140°; V: 140°							
Gray Scale	Red, Green and Blue each 16K							
Display Color	4096 Billion							
IP Rating	IP43							
Display Capability	Text, Graph and Video							

Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to SZLEDWORLD.