

## Application:

☐ Press Conference
 ☐ Wedding
 ☐ Outdoor Music Festival
 ☐ Store
 ☐ Exhibition Hall

## Technical Specifications(RHY Series Led Display P2.604):

| Pixel Pitch             | P2.604(indoor)         | P2.604 (outdoor)      |
|-------------------------|------------------------|-----------------------|
| LED type                | SMD1415                | SMD1515               |
| Pixel configuration     | 3-in-1 SMD             | 3-in-1 SMD            |
| Pixel density           | 147,456 pixels/m2      | 147,456 pixels/m2     |
| Module dimension(W*H)   | 250*250mm              | 250*250mm             |
| Module resolution       | 96*96dots              | 96*96dots             |
| Drive Method            | 1/24 scan              | 1/32 scan             |
| Maintenance             | Front & Rear           | Front & Rear          |
| Cabinet size (W*H)      | 500*500mm              | 500*500mm             |
| Cabinet depth           | 92mm                   | 92mm                  |
| Cabinet material        | Aluminum               | Aluminum              |
| Cabinet weight          | 7.5kg/pcs              | 6.5kg/pcs             |
| Brightness              | 4500 cd/m <sup>2</sup> | 800 cd/m <sup>2</sup> |
| Best Viewing Distance   | 2.6m to 26m            | 2.6m to 26m           |
| Viewing Angle           | 160 * 160              | 160 * 160             |
| Grey Level              | 16bits                 | 16bits                |
| Refresh Rate            | ≥3840HZ                | ≥3840HZ               |
| Power consumption(Avg.) | 68w/cabinet            | 68w/cabinet           |
| Power consumption(Max.) | 200w/cabinet           | 200w/cabinet          |
| Humidity-operating      | 10% ~ 95%              | 10% ~ 95%             |
| Operating Temperature   | -40° - 60° C           | -40° - 60° C          |
| Screen life             | ≥100000 hours          | ≥100000 hours         |
| Controlling System      | Sync or Async          | Sync or Async         |
| Certificates            | CE,RoHS,FCC,UL         | CE,RoHS,FCC,UL        |
| Ingress Protection (IP) | IP65                   | IP31                  |
| Warranty                | 2 Years                | 2 Years               |

Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to SZLEDWORLD.