

Application:

☐ Press Conference
 ☐ Wedding
 ☐ Outdoor Music Festival
 ☐ Store
 ☐ Exhibition Hall

Technical Specifications(RHY Series Led Display P3.91):

Pixel Pitch	P3.91(indoor)	P3.91 (outdoor)
LED type	SMD1921	SMD2121
Pixel configuration	3 in 1 SMD	3 in 1 SMD
Pixel density	65,536 pixels/m2	65,536 pixels/m2
Module dimension(W*H)	250*250mm	250*250mm
Module resolution	64*64dots	64*64dots
Drive Method	1/16 scan	1/16 scan
Maintenance	Front & Rear	Front & Rear
Cabinet size (W*H)	500*500mm	500*500mm
Cabinet depth	92mm	92mm
Cabinet material	Aluminum	Aluminum
Cabinet weight	7.5kg/pcs	6.5kg/pcs
Brightness	4500 cd/m ²	800 cd/m ²
Best Viewing Distance	4m to 40m	4m to 40m
Viewing Angle	160 * 160	160 * 160
Grey Level	16bits	16bits
Refresh Rate	7680HZ	7680HZ
Power consumption(Avg.)	68w/cabinet	68w/cabinet
Power consumption(Max.)	200w/cabinet	200w/cabinet
Humidity-operating	10% ~ 95%	10% ~ 95%
Operating Temperature	-40° - 60° C	-40° - 60° C
Screen life	≥100000 hours	≥100000 hours
Controlling System	Sync or Async	Sync or Async
Certificates	CE,RoHS,FCC,UL	CE,RoHS,FCC,UL
Ingress Protection (IP)	IP65	IP31
Warranty	2 Years	2 Years

Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to SZLEDWORLD.