

Application:

☐ Press Conference
 ☐ Wedding
 ☐ Outdoor Music Festival
 ☐ Store
 ☐ Exhibition Hall

Technical Specifications(RSD Series Led Display Indoor):

Pixel Pitch	P2.5
LED type	SMD1515
Pixel configuration	3-in-1 SMD
Pixel density	160000pixels/m ²
Module dimension(W*H)	250*250mm
Module resolution	100*100dots
Drive Method	1/25 scan
Maintenance	Front & Rear
Cabinet size (W*H)	500*500mm
Cabinet depth	75mm
Cabinet material	Aluminum
Cabinet weight	6.5kg/pcs
Brightness	800 cd/m ²
Best Viewing Distance	2.5 m to 25m
Viewing Angle	160 ° 160
Grey Level	16bits
Refresh Rate	≥3840HZ
Power consumption(Avg.)	68w/cabinet
Power consumption(Max.)	200w/cabinet
Humidity-operating	10% ~ 95%
Operating Temperature	-40° - 60° C
Screen life	≥100000 hours
Controlling System	Sync or Async
Certificates	CE, RoHS, FCC, UL
Ingress Protection (IP)	IP31
Warranty	2 Years
Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reservebyto SZLEDWORLD.	