

Application:

☐ Product Launch Event
 ☐ Wedding
 ☐ Outdoor Music Festival
 ☐ Store
 ☐ Assembly hall

Technical Specifications(RSK Series Led Display P1.56):

Pixel Pitch	P1.56
LED type	SMD1010
Pixel configuration	3-in-1 SMD
Pixel density	409,600 pixels/m ²
Module dimension(W*H)	250*250mm
Module resolution	160*160dots
Drive Method	1/40 scan
Maintenance	Front & Rear
Cabinet size (W*H)	500*500mm
Cabinet depth	70mm
Cabinet material	Aluminum
Cabinet weight	7.5kg/pcs
Brightness	600 cd/m ²
Best Viewing Distance	1.5m to 15m
Viewing Angle	160° * 160°
Grey Level	16bits
Refresh Rate	≥3840HZ
Power consumption(Avg.)	68w/cabinet
Power consumption(Max.)	200w/cabinet
Humidity-operating	10% ~ 95%
Operating Temperature	-40° - 60° C
Screen life	≥100000 hours
Controlling System	Sync or Async
Certificates	CE,RoHS,FCC,UL
Ingress Protection (IP)	IP31
Warranty	2 Years

Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to SZLEDWORLD.