

Smart Interactive Floor LED Display Indoor And Outdoor



Module & cabinet:



500*500 mm




500*1000 mm



Front maintenance

Features:

- Pixel pitch: Pixel pitch: LF2.5, LF2.976, LF3.91, LF4.68, LF5.2, LF6.25, LF7.8125, LF8.928;
- Module size: 250*250mm;
- Cabinet size: 500*500 mm/500*1000 mm
- Cabinet materials: aluminum and iron;
- Front maintenance;
- Super load-bearing;
- Silent heat dissipation;
- Thickness: 68/80mm ;



Application:

☐ Museum
 ☐ Runway
 ☐ Shopping Mall
 ☐ Business Actives
 ☐ Pop-up Shop

Technical Specifications(Floor LED Display):

Type	LF2. 5	LF2. 976	LF3. 91	LF4. 68	LF4. 68 Stairs	LF4. 81	LF5. 2	LF6. 25	LF7. 8125	LF8. 928	
Module resolution	100*100	84*84	64*64	64*32	64*32	52*52	48*48	40*40	32*32	28*28	
Module size	250*250mm	250*250mm	250*250mm	300*150mm	300*150mm	250*250mm	250*250mm	250*250mm	250*250mm	250*250mm	
Resolution	160000dots/m²	112896dots/m²	65025dots/m²	51200dots/m²	45796dots/m²	43264dots/m²	36864dots/m²	25600dots/m²	16384dots/m²	12544dots/m²	
Scan	1/25scan	1/14scan	1/16scan	1/8scan	1/8scan	1/13scan	1/6scan	1/10scan	1/4scan	1/4scan	
Brightness	Indoor:2000cd/m²	Indoor:2000cd/m²	Indoor:2000cd/m²	Indoor:2000cd/m²	Indoor:2000cd/m²	Indoor:2000cd/m²	Indoor:2000cd/m²	Indoor:2000cd/m²	Indoor:2000cd/m²	Indoor:2000cd/m²	
			Outdoor:4500cd/m²	Outdoor:4500cd/m²	Outdoor:4500cd/m²	Outdoor:4500cd/m²	Outdoor:4500cd/m²	Outdoor:5000cd/m²	Outdoor:5000cd/m²	Outdoor:5000cd/m²	
Cabinet size	500*500mm	500*500mm	500*500mm	600*600mm	1200*(300+150)mm	500*500mm	500*500mm	500*500mm	500*500mm	500*500mm	
	500*1000mm	500*1000mm	500*1000mm			500*1000mm	500*1000mm	500*1000mm	500*1000mm	500*1000mm	
Weight/Cabinet	25kg	25kg	25kg	25kg	55kg	25kg	25kg	25kg	25kg	25kg	
Refresh	1920/3840Hz	1920/3840Hz	1920/3840Hz	1920/3840Hz	1920/3840Hz	1920/3840Hz	1920/3840Hz	1920/3840Hz	1920/3840Hz	1920/3840Hz	
Working temperature	-20 ~ 65 °C										
Protection level	IndoorIP54, OutdoorIP68										
Defective ratio	4≤100000										
Protection technology	Anti-slip, moisture-proof, dust-proof, anti-corrosion, anti-static, anti-lightning, and has the functions of over-current, short-circuit, over-voltage, and under-voltage protection										
Cabinet material	Iron cabinet, Aluminum cabinet, Die-cast Aluminum cabinet										
Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to SZLEDWORLD.											