

## Application:

☐ Airport    ☐ Market    ☐ Grogshop    ☐ High-speed rail station    ☐ Offices    ☐ 4S shop  
☐ Shopping Guide    ☐ convention center    ☐ bank

## Technical Specifications(Pole LED Display):

| Pixel Pitch                                                                                                                      | P4                           |
|----------------------------------------------------------------------------------------------------------------------------------|------------------------------|
| LED type                                                                                                                         | SMD 1921                     |
| Pixel configuration                                                                                                              | 3-in-1 SMD                   |
| <a href="#">Pixel density</a>                                                                                                    | 62,500 pixels/m <sup>2</sup> |
| Module dimension(W*H)                                                                                                            | 320*160mm                    |
| Module resolution                                                                                                                | 80*40dots                    |
| Drive Method                                                                                                                     | 1/10 scan                    |
| Cabinet size (W*H)                                                                                                               | 640*1280mm or Customized     |
| Cabinet depth                                                                                                                    | 136mm                        |
| Cabinet material                                                                                                                 | Iron or aluminum             |
| Cabinet weight                                                                                                                   | 34kg/pcs                     |
| Brightness                                                                                                                       | ≥5500 cd/m2                  |
| <a href="#">Best Viewing Distance</a>                                                                                            | 4m to 40m                    |
| Power consumption (Avg.)                                                                                                         | 300w/cabinet                 |
| Power consumption (Max.)                                                                                                         | 800w/cabinet                 |
| <a href="#">Viewing Angle</a>                                                                                                    | 140 * 140                    |
| Grey Level                                                                                                                       | 14 Bit                       |
| <a href="#">Refresh Rate</a>                                                                                                     | 3840HZ~7680Hz                |
| Humidity-operating                                                                                                               | 10% ~ 95%                    |
| Operating Temperature                                                                                                            | -20° - 50° C                 |
| Screen life                                                                                                                      | ≥100000 hours                |
| Controlling System                                                                                                               | Sync or Async                |
| Certificates                                                                                                                     | CE, RoHS, FCC, UL            |
| Ingress Protection (IP)                                                                                                          | IP65                         |
| Warranty                                                                                                                         | 2 Years                      |
| Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to SZLEDWORLD. |                              |