

Application:

☐ Airport ☐ Market ☐ Grogshop ☐ High-speed rail station ☐ Offices ☐ 4S shop
☐ Shopping Guide ☐ convention center ☐ bank

Technical Specifications(Pole LED Display):

Pixel Pitch	P6.67
LED type	SMD 2727
Pixel configuration	3-in-1 SMD
Pixel density	22,500 pixels/m ²
Module dimension(W*H)	320*160mm
Module resolution	48*24dots
Drive Method	1/6 scan
Cabinet size (W*H)	640*1280mm or Customized
Cabinet depth	136mm
Cabinet material	Iron or aluminum
Cabinet weight	34kg/pcs
Brightness	≥5500 cd/m2
Best Viewing Distance	6m to 60m
Power consumption (Avg.)	300w/cabinet
Power consumption (Max.)	800w/cabinet
Viewing Angle	140 * 140
Grey Level	14 Bit
Refresh Rate	3840HZ~7680Hz
Humidity-operating	10% ~ 95%
Operating Temperature	-20° - 50° C
Screen life	≥100000 hours
Controlling System	Sync or Async
Certificates	CE, RoHs, FCC, UL
Ingress Protection (IP)	IP65
Warranty	2 Years
Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to SZLEDWORLD.	