

## Application:

☐ Store
 ☐ Fashion Pop-up Event
 ☐ Museum
 ☐ Airport
 ☐ exhibition

## Technical Specifications(Outdoor Cube LED DisplayP5):

| Specification                     | P5mm-Cube                             |
|-----------------------------------|---------------------------------------|
| Pixel Pitch                       | 5mm                                   |
| LED Configuration                 | SMD1921                               |
| LED Density (dot/m <sup>2</sup> ) | 40,000                                |
| Module Size                       | 320*160mm                             |
| Module Resolution                 | 64*32                                 |
| Cube Size                         | 320*320*320/640*640*640/960*960*960mm |
| Driving IC                        | 1/8 Scan                              |
| Hor. Viewing Angle                | 140°                                  |
| Vert. Viewing Angle               | 140°                                  |
| Best Viewing Distance             | 5 - 50m                               |
| Grey Level                        | 14 bits                               |
| Brightness                        | 5,500 cd/m <sup>2</sup>               |
| Brightness Adjustment             | 100-grade, Auto/Manual                |
| Brightness Uniformity             | >99%                                  |
| Input Voltage                     | DC5V                                  |
| Avg. Power Consumption            | 325 W/m <sup>2</sup>                  |
| Max. Power Consumption            | 970 W/m <sup>2</sup>                  |
| Operating Voltage                 | 100 - 240V / 50 - 60Hz                |
| Control System                    | NovaStar                              |
| Control Mode                      | Synchronous & Asynchronous            |
| Support Input                     | VGA, Video, DVI, MOV, MPG, DAT, VOB   |
| Lifetime                          | ≥100,000 hours                        |
| Blind Spot Rate                   | <0.00001                              |
| Working Temperature               | -20° C to +60° C                      |
| Working Humidity                  | 10% - 90% RH                          |
| Protection Rating                 | IP65                                  |
| Service Ways                      | Front                                 |

Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to SZLEDWORLD.