

Application:

☐ Store
 ☐ Fashion Pop-up Event
 ☐ Museum
 ☐ Airport
 ☐ exhibition

Technical Specifications(Rental Cube LED DisplayP2.6):

Item	P2.6
Pixel Pitch	2.604mm
LED Type	SMD1515
Module Resolution	96dots x 96dots
Driving Mode	1/32 scan
Module Pixels	9,216dots
Module Size (mm)	500 x 500
Cabinet Size (mm)	500 x 500
Cabinet Resolution (dots)	192 x 192
Pixel Density (dots/m ²)	147,456
Minimum Viewing Distance	≥4m
Brightness	600 - 800 nits
IP Grade	IP43
Refresh Rate	1920Hz - 7680Hz
Gray Scale	12 - 16 bits
Viewing Angle	160° (H) / 160° (V)
Maximum Power Consumption	520 (W/m ²)
Average Power Consumption	175 (W/m ²)
Input Voltage	AC110V - AC220V, 50/60Hz
Operating Temperature	-20° C ~ +50° C
Operating Humidity	10% - 90% RH
Cabinet Material	Die-casting Aluminum
Cabinet Weight	7.5kg/panel
Operating System	Windows (Win7, Win10, etc.)
Signal Source Compatibility	DVI HDMI1.3 DP1.2

Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to SZLEDWORLD.