

Application:

☐ Store
 ☐ Fashion Pop-up Event
 ☐ Museum
 ☐ Airport
 ☐ exhibition

Technical Specifications(Outdoor Cube LED DisplayP3.076):

Specification	P3.076mm-Cube
Pixel Pitch	3.076mm
LED Configuration	SMD1921
LED Density (dot/m ²)	105,625
Module Size	320*160mm
Module Resolution	104*52
Cube Size	320*320*320/640*640*640/960*960*960mm
Driving IC	1/13 Scan
Hor. Viewing Angle	140°
Vert. Viewing Angle	140°
Best Viewing Distance	3 - 30m
Grey Level	14 bits
Brightness	5,500 cd/m ²
Brightness Adjustment	100-grade, Auto/Manual
Brightness Uniformity	>99%
Input Voltage	DC5V
Avg. Power Consumption	325 W/m ²
Max. Power Consumption	970 W/m ²
Operating Voltage	100 - 240V / 50 - 60Hz
Control System	NovaStar
Control Mode	Synchronous & Asynchronous
Support Input	VGA, Video, DVI, MOV, MPG, DAT, VOB
Lifetime	≥100,000 hours
Blind Spot Rate	<0.00001
Working Temperature	-20° C to +60° C
Working Humidity	10% - 90% RH
Protection Rating	IP65
Service Ways	Front

Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to SZLEDWORLD.