

Application:

☐ Store
 ☐ Fashion Pop-up Event
 ☐ Museum
 ☐ Airport
 ☐ exhibition

Technical Specifications(Rental Cube LED DisplayP3.91):

Item	P3.91
Pixel Pitch	3.91mm
LED Type	SMD2020
Module Resolution	64dots x 64dots
Driving Mode	1/16 scan
Module Pixels	4,096dots
Module Size (mm)	500 x 500
Cabinet Size (mm)	500 x 500
Cabinet Resolution (dots)	128 x 128
Pixel Density (dots/m ²)	65,536
Minimum Viewing Distance	≥5m
Brightness	≥800 nits
IP Grade	IP43
Refresh Rate	1920Hz - 7680Hz
Gray Scale	12 - 16 bits
Viewing Angle	160° (H) / 160° (V)
Maximum Power Consumption	520 (W/m ²)
Average Power Consumption	175 (W/m ²)
Input Voltage	AC110V - AC220V, 50/60Hz
Operating Temperature	-20° C ~ +50° C
Operating Humidity	10% - 90% RH
Cabinet Material	Die-casting Aluminum
Cabinet Weight	7.5kg/panel
Operating System	Windows (Win7, Win10, etc.)
Signal Source Compatibility	DVI HDMI1.3 DP1.2

Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to SZLEDWORLD.