

Application:

☐ Store
 ☐ Fashion Pop-up Event
 ☐ Museum
 ☐ Airport
 ☐ exhibition

Technical Specifications(Indoor Cube LED Display P3):

Product Model	P3mm-Cube
Pixel Pitch	3mm
LED Configuration	SMD2020
LED Density (dot/m ²)	111,111 Pixels/m ²
Module Size	192*192mm
Cube Size	384*384*384mm/576*576*576mm/768*768*768
Driving Way	1/32scan
Hor. viewing angle	140°
Vert. viewing angle	140°
Best View Distance	3m - 30m
Grey Level	14 bits
Brightness	≥800 cd/m ²
Brightness Adjustment	100 grade auto/manual-adjustment
Brightness Uniformity	>99%
Input Voltage (AC)	DC5V
Avg Power Consumption	250 W/m ²
Max Power Consumption	580 W/m ²
Operation Power Voltage	100-240V / 50-60Hz
Control System	DVI card + Full color control card
Control Mode	Synchronous & asynchronous available
Support Input	VGA, Video, AVI, MOV, MPG, DAT, VOB etc.
Lifetime	>=100000hours
Blind Spot Rate	<0.00001
Working Temp	(-20)-(+60) Celsius degree
Working Humidity	10%-90%
Service Ways	Front
Waterproof Rating (Front/Rear)	IP54
Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to SZLEDWORLD.	