

Application:

☐ Store
 ☐ Fashion Pop-up Event
 ☐ Museum
 ☐ Airport
 ☐ exhibition

Technical Specifications(Indoor Cube LED Display P4):

Product Model	P4mm-Cube
Pixel Pitch	4mm
LED Configuration	SMD2020
LED Density (dot/m ²)	62,500 dots/m ²
Module Size	320×160mm
Cube Size	320*320*320mm/640*640*640mm/960*960*960
Driving Way	1/16 Scan
Hor. viewing angle	140°
Vert. viewing angle	140°
Best View Distance	4m - 40m
Grey Level	14 bits
Brightness	≥800 cd/m ²
Brightness Adjustment	100 grade auto/manual
Brightness Uniformity	>99%
Input Voltage (AC)	DC5V
Avg Power Consumption	250 W/m ²
Max Power Consumption	580 W/m ²
Operation Power Voltage	100-240V / 50-60Hz
Control System	DVI card + Full color control card
Control Mode	Synchronous & asynchronous
Support Input	VGA, Video, AVI, MOV, MPG, DAT, VOB
Lifetime	>100000 hours
Blind Spot Rate	<0.00001
Working Temp	(-20)~(+60) °C
Working Humidity	10% - 90%
Service Ways	Front
Waterproof Rating (Front/Rear)	P54
Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to SZLEDWORLD.	