

## Application:

☐ Product Launch Event
 ☐ Wedding
 ☐ Outdoor Music Festival
 ☐ Store
 ☐ Assembly hall

## Technical Specifications(RSK Series Led Display P3.91):

| Pixel Pitch             | P3.91(indoor)          | P3.91(outdoor)         |
|-------------------------|------------------------|------------------------|
| LED type                | SMD2121                | SMD1921                |
| Pixel configuration     | 3 in 1 SMD             | 3 in 1 SMD             |
| Pixel density           | 65,536 pixels/m2       | 65,536 pixels/m2       |
| Module dimension(W*H)   | 250*250mm              | 250*250mm              |
| Module resolution       | 64*64dots              | 64*64dots              |
| Drive Method            | 1/16 scan              | 1/16 scan              |
| Maintenance             | Front & Rear           | Front & Rear           |
| Cabinet size (W*H)      | 500*500mm              | 500*500mm              |
| Cabinet depth           | 70mm                   | 70mm                   |
| Cabinet material        | Aluminum               | Aluminum               |
| Cabinet weight          | 7.5kg/pcs              | 7.5kg/pcs              |
| Brightness              | 1000 cd/m <sup>2</sup> | 4500 cd/m <sup>2</sup> |
| Best Viewing Distance   | 4m to 40m              | 4m to 40m              |
| Viewing Angle           | 160 * 160              | 160 * 160              |
| Grey Level              | 16bits                 | 16bits                 |
| Refresh Rate            | 7680HZ                 | 7680HZ                 |
| Power consumption(Avg.) | 68w/cabinet            | 68w/cabinet            |
| Power consumption(Max.) | 200w/cabinet           | 200w/cabinet           |
| Humidity-operating      | 10% ~ 95%              | 10% ~ 95%              |
| Operating Temperature   | -40° - 60° C           | -40° - 60° C           |
| Screen life             | ≥100000 hours          | ≥100000 hours          |
| Controlling System      | Sync or Async          | Sync or Async          |
| Certificates            | CE,RoHS,FCC,UL         | CE,RoHS,FCC,UL         |
| Ingress Protection (IP) | IP31                   | IP65                   |
| Warranty                | 2 Years                | 2 Years                |

Notes:Specifications are for reference only.Please contact our salesperson for details.All rights are reserved to SZLEDWORLD.