

Application:

☐ Store
 ☐ Fashion Pop-up Event
 ☐ Museum
 ☐ Airport
 ☐ exhibition

Technical Specifications(Rental Cube LED Display):

Item	P1.95	P2.6	P2.9	P3.91
Pixel Pitch	1.95mm	2.604mm	2.976mm	3.91mm
LED Type	SMD1515	SMD1515	SMD1515	SMD2020
Module Resolution	128dots x 128dots	96dots x 96dots	84dots x 84dots	64dots x 64dots
Driving Mode	1/32 scan	1/32 scan	1/32 scan	1/16 scan
Module Pixels	16,384dots	9,216dots	7,056dots	4,096dots
Module Size (mm)	250 x 250	500 x 500	500 x 500	500 x 500
Cabinet Size (mm)	500 x 500	500 x 500	500 x 500	500 x 500
Cabinet Resolution (dots)	256 x 256	192 x 192	168 x 168	128 x 128
Pixel Density (dots/m ²)	161,291	147,456	112,896	65,536
Minimum Viewing Distance	≥3m	≥4m	≥4m	≥5m
Brightness	600 - 800 nits	600 - 800 nits	600 - 800 nits	≥800 nits
IP Grade	IP43	IP43	IP43	IP43
Refresh Rate	1920Hz - 7680Hz	1920Hz - 7680Hz	1920Hz - 7680Hz	1920Hz - 7680Hz
Gray Scale	12 - 16 bits	12 - 16 bits	12 - 16 bits	12 - 16 bits
Viewing Angle	160° (H) / 160° (V)	160° (H) / 160° (V)	160° (H) / 160° (V)	160° (H) / 160° (V)
Maximum Power Consumption	520 (W/m ²)	520 (W/m ²)	520 (W/m ²)	520 (W/m ²)
Average Power Consumption	175 (W/m ²)	175 (W/m ²)	175 (W/m ²)	175 (W/m ²)
Input Voltage	AC110V - AC220V, 50/60Hz	AC110V - AC220V, 50/60Hz	AC110V - AC220V, 50/60Hz	AC110V - AC220V, 50/60Hz
Operating Temperature	-20° C ~ +50° C	-20° C ~ +50° C	-20° C ~ +50° C	-20° C ~ +50° C
Operating Humidity	10% - 90% RH	10% - 90% RH	10% - 90% RH	10% - 90% RH
Cabinet Material	Die-casting Aluminum	Die-casting Aluminum	Die-casting Aluminum	Die-casting Aluminum
Cabinet Weight	7.5kg/panel	7.5kg/panel	7.5kg/panel	7.5kg/panel
Operating System	Windows (Win7, Win10, etc.)	Windows (Win7, Win10, etc.)	Windows (Win7, Win10, etc.)	Windows (Win7, Win10, etc.)
Signal Source Compatibility	DVI HDMI1.3 DP1.2	DVI HDMI1.3 DP1.2	DVI HDMI1.3 DP1.2	DVI HDMI1.3 DP1.2

Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to SZLEDWORLD.